

Lubricants Engineered for the Application

WearMaster® KF 245

E.P., Anti-Wear Conveyor Lubricant

WearMaster KF 245 is a premium product compounded for severe industrial applications where high loads and ambient conditions cause premature wear and failure to heavy-duty industrial conveyors. It contains a precise combination of ingredients including: top quality base oils, anti-wear and E.P. additives, rust inhibitors and a pour point depressant. WearMaster KF 245 does not contain moly solids, which can sometimes contribute to an undesirable buildup.

WearMaster KF 245 Light is compounded for use in low viscosity lube dispensing systems where the evaporative solvents in dry film lubes have become environmentally unacceptable.

TYPICAL SPECIFICATIONS	KF 245-LIGHT	KF 245
ISO Viscosity Grade	22	100
Viscosity Index	109	93
Viscosity cSt @ 40°C	22.1	102.1
Viscosity cSt @ 100°C	4.41	11.1
Flash Point, °F (°C), Min	378 (192)	464 (240)
Fire Point, °F (°C), Min	432 (222)	500 (260)
Rust inhibitor	Yes	Yes
Anti-wear additive	Yes	Yes
Extreme pressure additive	Yes	Yes
Color	Amber	Amber

WEARMASTER LUBRICANT APPLICATIONS INCLUDE:

OPEN RACE TROLLEY WHEELS • OPEN RACE GUIDE ROLLERS • SEALED TROLLEY WHEELS • CHAIN PINS • CHAIN LINKS • CHAIN ROLLERS AND BUSHINGS • RIDER PLATES AND WEAR BARS • SEALED ROLLERS AND BUSHINGS • DRIVE CHAINS • CABLE JOINTS • CASTER WHEELS • FLAT TOP AND SLAT WHEELS • RETRACTABLE DOG MECHANISMS • CARRIER KING PINS • RETRACTABLE DOG ACTUATOR LINKAGE