

## Lubricants Engineered for the Application

### WearMaster® KF 330 Series

High Performance Industrial Gear Lubricants

WearMaster KF 330 Gear Lubricants are designed for severe duty conditions. They offer excellent gear protection and extended service for multiple applications. The high viscosity index base oils and the sulfur, phosphorus type additive package make the WearMaster KF 330 E.P. Gear Lubricants ideal for application in worm, hypoid, bevel, spur, herring bone and helical gears. Other selected additives in the KF 330 Gear Lubricants offer water separation, rust protection and anti-foam characteristics.

WearMaster KF 330 Gear Lubricants meet the Cincinnati Milacron P35, P59, P63, P74, P77 and P78 specifications.

WearMaster KF 330 Gear Lubricants can be used in the following applications:

- Industrial applications where E.P. gear lubricants are required
- Steel mill gears, plain journal bearing gear boxes
- Oil Mist Systems
- Paper machine dryer bearings

TECHNICAL DATA					
	TYPICAL SPECS				
ISO Viscosity Grade	68	100	150	220	460
Viscosity Index	99	93	96	97	99
Viscosity cSt @ 40°C	67	102.1	150.7	219	454.7
Viscosity cSt @ 100°C	8.6	11.1	14.7	19	31.1
AGMA Classification	2EP	3EP	4EP	5EP	7EP
Flash Point, °F (°C), Min	439 (226)	464 (240)	446 (230)	460 (238)	435 (224)
Fire Point, °F (°C), Min	471 (244)	500 (260)	486 (252)	500 (260)	500 (260)
Rust inhibitor	Yes	Yes	Yes	Yes	Yes
Anti-wear additive	Yes	Yes	Yes	Yes	Yes
Extreme pressure additive	Yes	Yes	Yes	Yes	Yes
Color	Amber	Amber	Amber	Amber	Amber

**WEARMASTER LUBRICANT APPLICATIONS INCLUDE:**

OPEN RACE TROLLEY WHEELS • OPEN RACE GUIDE ROLLERS • SEALED TROLLEY WHEELS • CHAIN PINS • CHAIN LINKS • CHAIN ROLLERS AND BUSHINGS • RIDER PLATES AND WEAR BARS • SEALED ROLLERS AND BUSHINGS • DRIVE CHAINS • CABLE JOINTS • CASTER WHEELS • FLAT TOP AND SLAT WHEELS • RETRACTABLE DOG MECHANISMS • CARRIER KING PINS • RETRACTABLE DOG ACTUATOR LINKAGE