

Lubricants Engineered for the Application

WearMaster® KF 35

Dry Film Bonded Lubricant

WearMaster KF 35 is a bonded Moly Sulfide-based lubricant in a rapid evaporative rate carrier. Its primary applications are for chain and conveyor lubrication where the use of an oil-based lubricant is not desired, yet anti-wear and extreme pressure protection is needed. The dry film Moly lubricant bonds to the lubricated surface to provide positive lubrication. The solvent-based carrier helps to dissolve accumulated build-up, and the highly refined suspension grade Moly resists settling out. WearMaster KF-35 can be used in ambient temperature applications up to 255°F.

In addition, WearMaster KF 35 contains a special additive package to provide a high degree of rust and corrosion resistance, anti-wear protection and additional lubricity.

TYPICAL SPECIFICATIONS	
ISO Viscosity Grade	6
Viscosity cSt @ 40°C	6
Moly Solids, %	<2.0
Flash Point, °F (°C), Min	158 (70)
Fire Point, °F (°C), Min	158 (70)
Anti-wear additive	Yes
Extreme pressure additive	Yes
Color	Dark Gray

WEARMASTER LUBRICANT APPLICATIONS INCLUDE:

OPEN RACE TROLLEY WHEELS • OPEN RACE GUIDE ROLLERS • SEALED TROLLEY WHEELS • CHAIN PINS • CHAIN LINKS • CHAIN ROLLERS AND BUSHINGS • RIDER PLATES AND WEAR BARS • SEALED ROLLERS AND BUSHINGS • DRIVE CHAINS • CABLE JOINTS • CASTER WHEELS • FLAT TOP AND SLAT WHEELS • RETRACTABLE DOG MECHANISMS • CARRIER KING PINS • RETRACTABLE DOG ACTUATOR LINKAGE