

Lubricants Engineered for the Application

WearMaster® KF 39

Dry Film Silicone Lubricant

WearMaster KF 39 is a dry film silicone based lubricant in an evaporative carrier. Its primary applications are for chain and conveyor lubrication where the use of an oil-based lubricant is not desired yet anti-wear and lubrication protection is needed. WearMaster KF 39 dry film lubricant bonds to the lubricated surface and withstands extreme temperatures without flashpoint and firepoint concerns. The fluid carrier has a relatively low flashpoint, and the silicone lubricant is virtually non-flammable.

In addition WearMaster KF 39 contains only FDA approved ingredients for use in areas of possible incidental food contact.

TYPICAL SPECIFICATIONS	
ISO Viscosity Grade	6
Viscosity cSt @ 40°C	6
Lubricant components, %	3
Flash Point, °F (°C), Min	130 (54)
Fire Point, °F (°C), Min	132 (56)
Color	Clear

WEARMASTER LUBRICANT APPLICATIONS INCLUDE:

OPEN RACE TROLLEY WHEELS • OPEN RACE GUIDE ROLLERS • SEALED TROLLEY WHEELS • CHAIN PINS • CHAIN LINKS • CHAIN ROLLERS AND BUSHINGS • RIDER PLATES AND WEAR BARS • SEALED ROLLERS AND BUSHINGS • DRIVE CHAINS • CABLE JOINTS • CASTER WHEELS • FLAT TOP AND SLAT WHEELS • RETRACTABLE DOG MECHANISMS • CARRIER KING PINS • RETRACTABLE DOG ACTUATOR LINKAGE